

GSCELLTRACK/HD50

CellTrack HD 50 (Heavy Duty) 600mm x 400mm x 50mm anthracite grey panel



DESCRIPTION

CellTrack HD 50 (Heavy Duty) 600mm x 400mm x 50mm anthracite grey panel

SPECIFICATION

General information

Stock code GSCELLTRACK/HD50

Geocellular paving

Colour Anthracite grey (speckled)

Cell shape Hexaganol (Honeycomb)

Length 600 mm

Width 400 mm

Height 50 mm

Cell diameter 120 mm

UV stabilised

Weight per unit +/- 1.8kg

Weight per m2 +/- 7.5kg

Breaking strain (unfilled) +/- 200 T/m²

Breaking strain (Filled) +/- 500 T/m²

Connection system Integrated connection system





NOTES

CellTrack HD 50 is only suitable for applications where vehicle speeds are limited to 15mph and below.

Gravel pavers should be overfilled by approximately 10–20 mm (1–2 cm) above the top of the grid cells.

Why Overfill?

- To hide the grid: A slight overfill conceals the plastic structure of the paver, making the surface visually continuous with the surrounding area.
- To allow for settling and compaction: Gravel will settle over time due to foot or vehicle traffic. The overfill compensates for this, maintaining coverage and performance.
- To maintain a smooth surface: Without enough overfill, the tops of the grid can become exposed, especially in high-traffic areas, which may lead to discomfort, wear, or damage.

Packaging

Quantity	m ² per	Quantity per	m ² per full	Dimensions of pallet
per pallet	pallet	fill truck load	truck load	
176	42.24m ²	5,632 (32 pallets)	1351.57m ²	120cm x 80cm x 235cm (one-way pallet)

- 1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves the above data is current.
- 3. Installation details are available in the knowledge base.
- 4. All Geoworks products are supplied subject to our <u>Terms and Conditions of Sale.</u>

