

MultiTrack NW 13

MultiTrack NW 13 Nonwoven Geotextile, 2200N, 160g/m² - 5.25m x 100m roll



UK
CA CE

DESCRIPTION

MultiTrack NW 13 Nonwoven Geotextile, 2200N, 160g/m² - 5.25m x 100m roll

SPECIFICATION

General information

Stock code	GTNW/13
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	5.25m x 100m
Geotextile product range	MultiTrack

Geotextile properties

Tensile strength (MD)	EN ISO 10319	13kN/m
Tensile strength (CMD)	EN ISO 10319	13kN/m
Elongation at max load (MD)	EN ISO 10319	45%
Elongation at max load (CMD)	EN ISO 10319	55%
Static puncture resistance	EN ISO 12236	2.2kN
Dynamic perforation resistance	EN ISO 13433	21.5mm
CBR puncture resistance	EN ISO 12236	2200N

Dynamic cone drop	EN ISO 13433	21.5mm
Water permeability	EN ISO 11058	100L/m ² .s
Thickness under 2kPa	EN ISO 9863-1	1.45mm
Weight	EN ISO 9864	160g/m ²

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

