

## MultiTrack NW 15

MultiTrack NW 15 Nonwoven Geotextile, 2500N, 180g/m<sup>2</sup> - 5.25m x 100m roll



### DESCRIPTION

MultiTrack NW 15 Nonwoven Geotextile, 2500N, 180g/m<sup>2</sup> - 5.25m x 100m roll

## SPECIFICATION

### General information

Stock code	GTNW/15
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	5.25m x 100m
Geotextile product range	MultiTrack

### Geotextile properties

Tensile strength (MD)	EN ISO 10319	15kN/m
Tensile strength (CMD)	EN ISO 10319	15kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Static puncture resistance	EN ISO 12236	2.5kN
Dynamic perforation resistance	EN ISO 13433	20mm
CBR puncture resistance	EN ISO 12236	2500N

<b>Dynamic cone drop</b>	EN ISO 13433	20mm
<b>Water permeability</b>	EN ISO 11058	90L/m <sup>2</sup> .s
<b>Characteristic opening size</b>	EN ISO 12956	90µm
<b>Thickness under 2kPa</b>	EN ISO 9863-1	1.25mm
<b>Weight</b>	EN ISO 9864	180g/m <sup>2</sup>

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

