

MultiTrack NW 18

MultiTrack NW 18 Nonwoven Geotextile, 3000N, 215g/m² - 5.25m x 100m roll



UK
CA CE

DESCRIPTION

MultiTrack NW 18 Nonwoven Geotextile, 3000N, 215g/m² - 5.25m x 100m roll

SPECIFICATION

General information

Stock code	GTNW/18
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	5.25m x 100m

Geotextile properties

Tensile strength (MD)	EN ISO 10319	18kN/m
Tensile strength (CMD)	EN ISO 10319	18kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Static puncture resistance	EN ISO 12236	3kN
Dynamic perforation resistance	EN ISO 13433	16.5mm
CBR puncture resistance	EN ISO 12236	3000N
Dynamic cone drop	EN ISO 13433	16.5mm

Water permeability	EN ISO 11058	70L/m ² .s
Characteristic opening size	EN ISO 12956	85µm
Thickness under 2kPa	EN ISO 9863-1	1.4mm
Weight	EN ISO 9864	215g/m ²

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

