

## MultiTrack NW 20

MultiTrack NW 20 Nonwoven Geotextile, 3100N, 235g/m<sup>2</sup> - 5.25m x 100m roll



UK  
CA CE

### DESCRIPTION

MultiTrack NW 20 Nonwoven Geotextile, 3100N, 235g/m<sup>2</sup> - 5.25m x 100m roll

## SPECIFICATION

### General information

Stock code	GTNW/20
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	5.25m x 100m
Geotextile product range	MultiTrack

### Geotextile properties

Tensile strength (MD)	EN ISO 10319	20kN/m
Tensile strength (CMD)	EN ISO 10319	20kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Static puncture resistance	EN ISO 12236	3.1kN
Dynamic perforation resistance	EN ISO 13433	16mm
CBR puncture resistance	EN ISO 12236	3100N

<b>Dynamic cone drop</b>	EN ISO 13433	16mm
<b>Water permeability</b>	EN ISO 11058	65L/m <sup>2</sup> .s
<b>Characteristic opening size</b>	EN ISO 12956	70µm
<b>Thickness under 2kPa</b>	EN ISO 9863-1	1.4mm
<b>Weight</b>	EN ISO 9864	235g/m <sup>2</sup>

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

