

MultiTrack 1000®

MultiTrack 1000® Nonwoven Geotextile, 1500N, 100g/m² - 4.5m x 100m roll (mini packs also available)



UK
CA CE

DESCRIPTION

MultiTrack 1000® Nonwoven Geotextile, 1500N, 100g/m² - 4.5m x 100m roll (mini packs also available)

SPECIFICATION

General information

Stock code	GTNW/MULTITRACK
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	4.5m x 100m
Geotextile product range	MultiTrack

Geotextile properties

Tensile strength (MD)	EN ISO 10319	8kN/m
Tensile strength (CMD)	EN ISO 10319	8kN/m
Elongation at max load (MD)	EN ISO 10319	45%
Elongation at max load (CMD)	EN ISO 10319	55%
Static puncture resistance	EN ISO 12236	1.5kN
Dynamic perforation resistance	EN ISO 13433	34mm
CBR puncture resistance	EN ISO 12236	1500N

Dynamic cone drop	EN ISO 13433	34mm
Water permeability	EN ISO 11058	110L/m ² .s
Characteristic opening size	EN ISO 12956	120µm
Thickness under 2kPa	EN ISO 9863-1	1mm
Weight	EN ISO 9864	100g/m ²

NOTES

Alternate mini pack roll sizes

Mini pack rolls also available:

Stock code	Mini pack roll size
GTNW/MULTI/1X14	1m x 14m
GTNW/MULTI/4.5X10	4.5m x 10m
GTNW/MULTI/2.25X25	2.25m x 25m
GTNW/MULTI/2.25X50	2.25m x 50m

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

