

MultiTrack 700

MultiTrack 700 Nonwoven Geotextile, 1000N, 80g/m² - 4.5m x 100m roll



DESCRIPTION

MultiTrack 700 Nonwoven Geotextile, 1000N, 80g/m² - 4.5m x 100m roll

SPECIFICATION

General information

Stock code	GTNW/MULTI/700
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	4.5m x 100m
Geotextile product range	MultiTrack

Geotextile properties

Tensile strength (MD)	EN ISO 10319	6kN/m
Tensile strength (CMD)	EN ISO 10319	6kN/m
Elongation at max load (MD)	EN ISO 10319	45%
Elongation at max load (CMD)	EN ISO 10319	55%
Static puncture resistance	EN ISO 12236	1kN
Dynamic perforation resistance	EN ISO 13433	40mm
CBR puncture resistance	EN ISO 12236	1000N

Dynamic cone drop	EN ISO 13433	40mm
Water permeability	EN ISO 11058	120L/m ² .s
Characteristic opening size	EN ISO 12956	140µm
Thickness under 2kPa	EN ISO 9863-1	0.85mm
Weight	EN ISO 9864	80g/m ²

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

