

MultiTrack 700

MultiTrack 700 Nonwoven Geotextile, 1000N, 80g/m² - 4.5m x 100m roll



CHARACTERISTIC	VALUE
Description	MultiTrack 700 Nonwoven Geotextile, 1000N, 80g/m ² - 4.5m x 100m roll

SPECIFICATION

GENERAL INFORMATION

Stock code	GTNW/MULTI/700
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	4.5m x 100m
Geotextile product range	MultiTrack

GEOTEXTILE PROPERTIES

Tensile strength (MD)	EN ISO 10319	6kN/m
Tensile strength (CMD)	EN ISO 10319	6kN/m
Elongation at max load (MD)	EN ISO 10319	45%
Elongation at max load (CMD)	EN ISO 10319	55%
Dynamic perforation resistance	EN ISO 13433	40mm
CBR puncture resistance	EN ISO 12236	1000N
Dynamic cone drop	EN ISO 13433	40mm
Water permeability	EN ISO 11058	120L/m ² .s
Characteristic opening size	EN ISO 12956	140µm
Thickness under 2kPa	EN ISO 9863-1	0.85mm
Weight	EN ISO 9864	80g/m ²

- Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- Installation details are available in the [knowledge base](#).
- All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).
- Some imagery within our materials is illustrative in nature and may not depict the exact product supplied.