

Root-Tex 30 (discontinued)

MultiTrack SNW 40 UV Superior Nonwoven Geotextile, 4000N, 300g/m² - 5.25m x 100m roll (other roll sizes available)



UK
CA CE

DESCRIPTION

MultiTrack SNW 40 UV Superior Nonwoven Geotextile, 4000N, 300g/m² - 5.25m x 100m roll (other roll sizes available)

SUPERSEDED BY

STOCK CODE

GTSNW/40UV

DESCRIPTION

MultiTrack SNW 40 UV Superior Nonwoven Geotextile, 4000N, 300g/m² - 5.25m x 100m roll (other roll sizes available)

SPECIFICATION

General information

Stock code

GTROOTTEX30

Range

MultiTrack

Third party certified

CE
UKCA

Roll sizes

5.25m x 100m
2.5m x 25m
2.62m x 100m

Geotextile product range

MultiTrack

Geotextile properties

Tensile strength (MD)	EN ISO 10319	22kN/m
Tensile strength (CMD)	EN ISO 10319	22kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Static puncture resistance	EN ISO 12236	4kN
Dynamic perforation resistance	EN ISO 13433	12mm
CBR puncture resistance	EN ISO 12236	4000N
Dynamic cone drop	EN ISO 13433	12mm
Water permeability	EN ISO 11058	60L/m ² .s
Characteristic opening size	EN ISO 12956	90µm
Thickness under 2kPa	EN ISO 9863-1	2.4mm
Weight	EN ISO 9864	300g/m ²

NOTES

Oil retention (l/10m²): >6

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

