

Root-Tex 30 (discontinued)

Superior Nonwoven Geotextile, 4000N, 300g/m² - 5.25m x 100m roll
(other roll sizes available)



SUPERSEDED BY

Stock code	Description
GTSNW/40UV	MultiTrack SNW 40 UV Superior Nonwoven Geotextile, 4000N, 300g/m ² - 5.25m x 100m roll (other roll sizes available)

CHARACTERISTIC	VALUE
Description	Superior Nonwoven Geotextile, 4000N, 300g/m ² - 5.25m x 100m roll (other roll sizes available)

SPECIFICATION

GENERAL INFORMATION

Stock code	GTROOTTEX30
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	5.25m x 100m 2.5m x 25m 2.62m x 100m
Geotextile product range	MultiTrack

GEOTEXTILE PROPERTIES

Tensile strength (MD)	EN ISO 10319	22kN/m
Tensile strength (CMD)	EN ISO 10319	22kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Dynamic perforation resistance	EN ISO 13433	12mm
CBR puncture resistance	EN ISO 12236	4000N
Dynamic cone drop	EN ISO 13433	12mm
Water permeability	EN ISO 11058	60L/m ² .s
Characteristic opening size	EN ISO 12956	90µm
Thickness under 2kPa	EN ISO 9863-1	2.4mm
Weight	EN ISO 9864	300g/m ²

NOTES

Oil retention (l/10m²): >6

- ▶ Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ Installation details are available in the [knowledge base](#).
- ▶ All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).
- ▶ Some imagery within our materials is illustrative in nature and may not depict the exact product supplied.