

FasTrack 1800 (discontinued)

FasTrack 1800 Woven Geotextile, 1900N, 85g/m² - 4.5m x 100m roll



SUPERSEDED BY

Stock code	Description	
GTSG/FASTRACK/609	FasTrack 609 Woven Geotextile, 1500N, 75g/m² - 4.5m x 100m roll (mini packs and folded rolls also available)	

CHARACTERISTIC	VALUE
Description	FasTrack 1800 Woven Geotextile, 1900N, 85g/m 2 - 4.5m x 100m roll

SPECIFICATION

GENERAL INFORMATION

Stock code	GTSG/FASTRACK/1
	800
Range	FasTrack
Third party	UKCA
certified	CE
Roll sizes	4.5m x 100m
Geotextile product	FasTrack
range	





GEOTEXTILE PROPERTIES

Material		Polypropylene
		3
Tensile strength	EN ISO 10319	18kN/m
(MD)	EN 130 10319	
Tensile strength	EN 100 40040	12kN/m
(CMD)	EN ISO 10319	
Elongation at max	EN 160 10010	25%
load (MD)	EN ISO 10319	
Elongation at max	EN ICO 10010	25%
load (CMD)	EN ISO 10319	
Dynamic		18mm
perforation	EN ISO 13433	
resistance		
CBR puncture	EN 100 12220	1900N
resistance	EN ISO 12236	
Dynamic cone drop	p EN ISO 13433	18mm
Water permeability	y EN ISO 11058	18L/m².s
Characteristic	EN ISO 12956	200µm
opening size	EIN 130 12950	
Weight	EN ISO 9864	85g/m²

- Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- Installation details are available in the <u>knowledge base</u>.

 All Geoworks products are supplied subject to our <u>Terms and Conditions of Sale</u>.
- Some imagery within our materials is illustrative in nature and may not depict the exact product supplied.



