

# FasTrack 1800 (discontinued)

FasTrack 1800 Woven Geotextile, 1900N, 85g/m<sup>2</sup> - 4.5m x 100m roll



### **SUPERSEDED BY**

Stock code	Description
GTSG/FASTRACK/609	FasTrack 609 Woven Geotextile, 1500N, 75g/m² - 4.5m x 100m roll (mini packs and folded rolls also available)

CHARACTERISTIC	VALUE
Description	FasTrack 1800 Woven Geotextile, 1900N, $85g/m^2 - 4.5m \times 100m \text{ roll}$

## **SPECIFICATION**





### **GENERAL INFORMATION**

Stock code	GTSG/FASTRACK/18
	00
Range	FasTrack
Third party certified	UKCA
	CE
Roll sizes	4.5m x 100m
Geotextile product	FasTrack
range	

#### **GEOTEXTILE PROPERTIES**

Material		Polypropylene
Tensile strength (MD)	EN ISO 10319	18kN/m
Tensile strength (CMD)	EN ISO 10319	12kN/m
Elongation at max load (MD)	EN ISO 10319	25%
Elongation at max load (CMD)	EN ISO 10319	25%
Dynamic perforation resistance	EN ISO 13433	18mm
CBR puncture resistance	EN ISO 12236	1900N
Dynamic cone drop	EN ISO 13433	18mm
Water permeability	EN ISO 11058	18L/m².s
Characteristic opening size	EN ISO 12956	200μm
Weight	EN ISO 9864	85g/m²

- Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without
- It is the responsibility of all users to satisfy themselves the above data is current.
- Installation details are available in the knowledge base.
- All Geoworks products are supplied subject to our <u>Terms and Conditions of Sale.</u>
  Some imagery within our materials is illustrative in nature and may not depict the exact product supplied.



