

FasTrack 609®

FasTrack 609 Woven Geotextile, 1500N, 75g/m² - 4.5m x 100m roll
(mini packs and folded rolls also available)



CHARACTERISTIC	VALUE
Description	FasTrack 609 Woven Geotextile, 1500N, 75g/m ² - 4.5m x 100m roll (mini packs and folded rolls also available)

SPECIFICATION

GENERAL INFORMATION

Stock code	GTSG/FASTRACK/609
Range	FasTrack
Third party certified	UKCA CE
Roll sizes	1m x 14m 2.25m x 25m 2.25m x 50m 4.5m x 11m 4.5m x 100m
Geotextile product range	FasTrack

GEOTEXTILE PROPERTIES

Material		Polypropylene
Tensile strength (MD)	EN ISO 10319	18kN/m
Tensile strength (CMD)	EN ISO 10319	10kN/m
Elongation at max load (MD)	EN ISO 10319	25%
Elongation at max load (CMD)	EN ISO 10319	25%
Dynamic perforation resistance	EN ISO 13433	19mm
CBR puncture resistance	EN ISO 12236	1500N
Dynamic cone drop	EN ISO 13433	19mm
Water permeability	EN ISO 11058	16L/m ² .s
Characteristic opening size	EN ISO 12956	300µm
Weight	EN ISO 9864	75g/m ²

NOTES

Mini pack and mini roll sizes:

Stock code	Mini roll sizes
GTSG/FAST/1X14A	1m x 14m

Stock code	Mini roll sizes
GTSG/FAST/2.25X25A	2.25m x 25m
GTSG/FAST/2.25X50A	2.25m x 50m

Stock code	Mini pack sizes
GTSG/FAST/4.5X11A	4.5m x 11m folded for convenient transport.

- ▶ Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ Installation details are available in the [knowledge base](#).
- ▶ All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).
- ▶ Some imagery within our materials is illustrative in nature and may not depict the exact product supplied.