

## MultiTrack SNW 120

MultiTrack SNW 120 Superior Nonwoven Geotextile, 11500N,  
1000g/m<sup>2</sup> - 5.25m x 35m roll



CHARACTERISTIC	VALUE
Description	MultiTrack SNW 120 Superior Nonwoven Geotextile, 11500N, 1000g/m <sup>2</sup> - 5.25m x 35m roll

## SPECIFICATION

### GENERAL INFORMATION

Stock code	GTSNW/120
Range	MultiTrack
Third party certified	CE UKCA
Geotextile product range	MultiTrack

### GEOTEXTILE PROPERTIES

Tensile strength (MD)	EN ISO 10319	70kN/m
Tensile strength (CMD)	EN ISO 10319	70kN/m
Elongation at max load (MD)	EN ISO 10319	70%
Elongation at max load (CMD)	EN ISO 10319	70%
CBR puncture resistance	EN ISO 12236	11500N
Dynamic cone drop	EN ISO 13433	0mm
Water permeability	EN ISO 11058	20L/m <sup>2</sup> .s

## NOTES

Product may be subject to longer lead times, contact the Wrekin Geosynthetics team for details.

- Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- Installation details are available in the [knowledge base](#).
- All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).
- Some imagery within our materials is illustrative in nature and may not depict the exact product supplied.