


SX Composite 3030

SX Composite 3030 composed of a thermally bonded SX Geogrid and Geotextile - 5.2m x 50m roll



DESCRIPTION

SX Composite 3030 composed of a thermally bonded SX Geogrid and Geotextile - 5.2m x 50m roll

SPECIFICATION

General information

Stock code	GGC/COMBSX30/5.2X50
Range	SX Grid
Third party certified	CE
Roll sizes	5.25m x 50m
Geogrid product range	SX Grid

Geogrid properties

Tensile strength (MD)	EN ISO 10319	30kN/m
Tensile strength (CMD)	EN ISO 10319	30kN/m
Tensile load (2% strain) (MD)	EN ISO 10319	11kN/m
Tensile load (2% CMD)	EN ISO 10319	11kN/m
Tensile load (5% strain) (MD)	EN ISO 10319	21kN/m
Tensile load (5% CMD)	EN ISO 10319	21kN/m
Aperture opening size		38mm x 38mm

Geotextile properties

Material		Polypropylene
Tensile strength (MD)	EN ISO 10319	10kN/m
Tensile strength (CMD)	EN ISO 10319	10kN/m
Elongation at max load (MD)	EN ISO 10319	40%
Elongation at max load (CMD)	EN ISO 10319	90%
Static puncture resistance	EN ISO 12236	1.5kN
CBR puncture resistance	EN ISO 12236	1500N

NOTES

Weight: 114kg \pm 10%

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

