

MultiTrack SNW 40 UV

MultiTrack SNW 40 UV Superior Nonwoven Geotextile, 4000N, 300g/m² - 5.25m x 100m roll (other roll sizes available)



DESCRIPTION

MultiTrack SNW 40 UV Superior Nonwoven Geotextile, 4000N, 300g/m² - 5.25m x 100m roll (other roll sizes available)

SPECIFICATION

General information

Stock code	GTSNW/40UV
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	5.25m x 100m 2.5m x 25m 2.62m x 100m
Geotextile product range	MultiTrack

Geotextile properties

Tensile strength (MD)	EN ISO 10319	22kN/m
Tensile strength (CMD)	EN ISO 10319	22kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Static puncture resistance	EN ISO 12236	4kN
Dynamic perforation resistance	EN ISO 13433	12mm

CBR puncture resistance	EN ISO 12236	4000N
Dynamic cone drop	EN ISO 13433	12mm
Water permeability	EN ISO 11058	60L/m ² .s
Characteristic opening size	EN ISO 12956	90µm
Thickness under 2kPa	EN ISO 9863-1	2.4mm
Weight	EN ISO 9864	300g/m ²

NOTES

Oil retention (l/10m²): >6

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

