

MultiTrack SNW 80

MultiTrack SNW 80 Superior Nonwoven Geotextile, 8000N, 650g/m² - 5.25m x 50m roll



UK
CA CE

DESCRIPTION

MultiTrack SNW 80 Superior Nonwoven Geotextile, 8000N, 650g/m² - 5.25m x 50m roll

SPECIFICATION

General information

| | |
|--------------------------|-------------|
| Stock code | GTSNW/80 |
| Range | MultiTrack |
| Third party certified | CE UKCA |
| Roll sizes | 5.25m x 50m |
| Geotextile product range | MultiTrack |

Geotextile properties

| | | |
|--------------------------------|--------------|--------|
| Tensile strength (MD) | EN ISO 10319 | 45kN/m |
| Tensile strength (CMD) | EN ISO 10319 | 45kN/m |
| Elongation at max load (MD) | EN ISO 10319 | 65% |
| Elongation at max load (CMD) | EN ISO 10319 | 70% |
| Dynamic perforation resistance | EN ISO 13433 | 2mm |
| CBR puncture resistance | EN ISO 12236 | 8000N |
| Dynamic cone drop | EN ISO 13433 | 2mm |

| | | |
|------------------------------------|---------------|-----------------------|
| Water permeability | EN ISO 11058 | 30L/m ² .s |
| Characteristic opening size | EN ISO 12956 | 65µm |
| Thickness under 2kPa | EN ISO 9863-1 | 4.8mm |
| Weight | EN ISO 9864 | 650g/m ² |

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

