


## ProtectaWeb 75

ProtectaWeb 75mm deep HDPE geocellular confinement system



### DESCRIPTION

ProtectaWeb 75mm deep HDPE geocellular confinement system

## SPECIFICATION

### General information

Stock code

Protectaweb/75

Range

ProtectaWeb

### Geocell

Material

High density polyethylene

Colour

Black

Density (g/cm<sup>3</sup>)

≥0.94

Carbon black content (%)

≥1.5

Tensile strength (MD)

20 kN/m

Tensile strength of perforated strip  
MD (kN/m)

10 kN/m

Elongation at max load

15%

Seam Peel Strength<sup>3</sup> (N/100mm  
depth cell)

≥1420

Bonded ranges (mm)

356±2.5

<b>Cell depth</b>	75 mm
<b>Expanded cell width</b>	260 mm
<b>Expanded cell length</b>	224 mm
<b>Number of cells per section</b>	330
<b>Expanded section width</b>	2.71 m
<b>Expanded section length</b>	7.38 m
<b>Expanded section area</b>	20 m <sup>2</sup>

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

