

GSCELLTRACK/LP50BB

Celltrack 50 1,200mm x 800mm x 50mm black large panel



CHARACTERISTIC

VALUE

Description

Celltrack 50 1,200mm x 800mm x 50mm black large panel

GEOCELLULAR PAVING

SPECIFICATION

GENERAL INFORMATION

Stock code	GSCELLTRACK/LP5
	OBB

Material	100% recycled High	
	Density	
	Polyethylene	
	(HDPE)	
Colour	Black	
Cell shape	Hexaganol	
	(Honeycomb)	
Length	1,200 mm	
Width	800 mm	
Height	50 mm	
Cell diameter	60 mm	
Open space	>90%	
UV	UV stabiliser	
Weight per unit	+/- 4.1kg	
Weight per m2	+/- 4.27kg	
Breaking strain	+/- 105 t/m2 (PTV	
(unfilled)	828)	
Biological	Very high	
resistance		
Chemical	Very high	
resistance		
Connection system	Integrated	
	connection system	

NOTES

Tel: 01543 440 480 Fax: 01543 440 444 info@geoworks.eco geoworks.eco





This is the large panel variant of CellTrack, with panels available in 1,200mm x 800mm sections and depth options of either 38mm or 50mm, allowing much quicker coverage. <u>A small panel variant is available</u>.

Gravel pavers should be overfilled by approximately 10–20 mm (1–2 cm) above the top of the grid cells.

Why Overfill?

- ► To hide the grid: A slight overfill conceals the plastic structure of the paver, making the surface visually continuous with the surrounding area.
- ► To allow for settling and compaction: Gravel will settle over time due to foot or vehicle traffic. The overfill compensates for this, maintaining coverage and performance.
- ► To maintain a smooth surface: Without enough overfill, the tops of the grid can become exposed, especially in high-traffic areas, which may lead to discomfort, wear, or damage.

PACKAGING:

Quantity per	m ² per	Quantity per fill truck	m ² per full truck	Dimensions of pallet
pallet	pallet	load	load	
45	43.2m ²	1440 (32 pallets)	1,382.4m ²	120cm x 80cm x 240cm (one-way pallet)

- Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- Installation details are available in the knowledge base.
- All Geoworks products are supplied subject to our <u>Terms and Conditions of Sale.</u>
- Some imagery within our materials is illustrative in nature and may not depict the exact product supplied.

Tel: 01543 440 480 Fax: 01543 440 444 info@geoworks.eco geoworks.eco



