

## GSCELLTRACK/HD100

CellTrack HD 100 (Heavy Duty) 600mm x 400mm x 100mm anthracite grey panel



### DESCRIPTION

CellTrack HD 100 (Heavy Duty) 600mm x 400mm x 100mm anthracite grey panel

## SPECIFICATION

### General information

**Stock code** GSCELLTRACK/HD100

### Geocellular paving

<b>Material</b>	50% recycled PE/PP (100% recyclable)
<b>Colour</b>	Anthracite grey (speckled)
<b>Cell shape</b>	Hexagonal (Honeycomb)
<b>Length</b>	600 mm
<b>Width</b>	400 mm
<b>Height</b>	100 mm
<b>Cell diameter</b>	120 mm
<b>UV</b>	UV stabilised
<b>Weight per unit</b>	+/- 3.4kg
<b>Weight per m2</b>	+/- 14.18kg
<b>Breaking strain (unfilled)</b>	+/- 200 T/m <sup>2</sup>
<b>Breaking strain (Filled)</b>	+/- 500 T/m <sup>2</sup>

## NOTES

Gravel pavers should be overfilled by approximately 10–20 mm (1–2 cm) above the top of the grid cells.

### Why Overfill?

- To hide the grid: A slight overfill conceals the plastic structure of the paver, making the surface visually continuous with the surrounding area.
- To allow for settling and compaction: Gravel will settle over time due to foot or vehicle traffic. The overfill compensates for this, maintaining coverage and performance.
- To maintain a smooth surface: Without enough overfill, the tops of the grid can become exposed, especially in high-traffic areas, which may lead to discomfort, wear, or damage.

## PACKAGING

Quantity per pallet	m <sup>2</sup> per pallet	Quantity per full truck load	m <sup>2</sup> per full truck load	Dimensions of pallet
88	21.1m <sup>2</sup>	2,816 (32 pallets)	675.3m <sup>2</sup>	120cm x 80cm x 231cm (one-way pallet)

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available in the [knowledge base](#).
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).