

GSCELLTRACK/HD100

CellTrack HD 100 (Heavy Duty) 600mm x 400mm x 100mm anthracite grey panel



CHARACTERISTIC	VALUE
Description	CellTrack HD 100 (Heavy Duty) 600mm x 400mm x 100mm anthracite grey panel

SPECIFICATION

GENERAL INFORMATION

Stock code	GSCELLTRACK/HD1
	00

GEOCELLULAR PAVING

Material	50% recycled	
	PE/PP (100%	
	recyclable)	
Colour	Anthracite grey	
	(speckled)	
Cell shape	Hexaganol	
	(Honeycomb)	
Length	600 mm	
Width	400 mm	
Height	100 mm	
Cell diameter	120 mm	
UV	UV stabilised	
Weight per unit	+/- 3.4kg	
Weight per m2	+/- 14.18kg	
Breaking strain	+/- 200 T/m²	
(unfilled)		
Breaking strain	+/- 500 T/m²	
(Filled)		
Connection system	Integrated	
	connection system	

NOTES

Gravel pavers should be overfilled by approximately 10-20 mm (1-2 cm) above the top of the grid cells.

Why Overfill?

Tel: 01543 440 480 Fax: 01543 440 444 info@geoworks.eco geoworks.eco





- ► To hide the grid: A slight overfill conceals the plastic structure of the paver, making the surface visually continuous with the surrounding area.
- ► To allow for settling and compaction: Gravel will settle over time due to foot or vehicle traffic. The overfill compensates for this, maintaining coverage and performance.
- ► To maintain a smooth surface: Without enough overfill, the tops of the grid can become exposed, especially in high-traffic areas, which may lead to discomfort, wear, or damage.

PACKAGING

Quantity per pallet	m ² per pallet	Quantity per fill truck load	m ² per full truck load	Dimensions of pallet
88	21.1m ²	2,816 (32 pallets)	675.3m ²	120cm x 80cm x 231cm (one-way pallet)

- Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- Installation details are available in the knowledge base.
- ▶ All Geoworks products are supplied subject to our <u>Terms and Conditions of Sale.</u>
- ▶ Some imagery within our materials is illustrative in nature and may not depict the exact product supplied.

Tel: 01543 440 480 Fax: 01543 440 444 info@geoworks.eco geoworks.eco



