

## MultiTrack NW 18

MultiTrack NW 18 Nonwoven Geotextile, 3000N, 215g/m<sup>2</sup> - 5.25m x 100m roll



UK  
CA CE

### DESCRIPTION

MultiTrack NW 18 Nonwoven Geotextile, 3000N, 215g/m<sup>2</sup> - 5.25m x 100m roll

## SPECIFICATION

### General information

Stock code	GTNW/18
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	5.25m x 100m

### Geotextile properties

Tensile strength (MD)	EN ISO 10319	18kN/m
Tensile strength (CMD)	EN ISO 10319	18kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Dynamic perforation resistance	EN ISO 13433	16.5mm
CBR puncture resistance	EN ISO 12236	3000N
Dynamic cone drop	EN ISO 13433	16.5mm
Water permeability	EN ISO 11058	70L/m <sup>2</sup> .s

<b>Characteristic opening size</b>	EN ISO 12956	85µm
<b>Thickness under 2kPa</b>	EN ISO 9863-1	1.4mm
<b>Weight</b>	EN ISO 9864	215g/m <sup>2</sup>

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

