


FasTrack 18/18 B

FasTrack 1818B Woven Geotextile, 2000N, 91g/m² - 5.25m x 100m roll



DESCRIPTION

FasTrack 1818B Woven Geotextile, 2000N, 91g/m² - 5.25m x 100m roll

SPECIFICATION

General information

Stock code	GTSG/FASTRACK/1818B	
Range	FasTrack	
Third party certified	UKCA CE	
Roll sizes	5.25m x 100m	
Geotextile product range	FasTrack	

Geotextile properties

Material	Polypropylene	
Tensile strength (MD)	EN ISO 10319	17.25kN/m
Tensile strength (CMD)	EN ISO 10319	17.25kN/m
Elongation at max load (MD)	EN ISO 10319	26%
Elongation at max load (CMD)	EN ISO 10319	26%
Static puncture resistance	EN ISO 12236	2kN
Dynamic perforation resistance	EN ISO 13433	16mm

CBR puncture resistance	EN ISO 12236	2000N
Dynamic cone drop	EN ISO 13433	16mm
Water permeability	EN ISO 11058	23L/m ² .s
Characteristic opening size	EN ISO 12956	305µm
Thickness under 2kPa	EN ISO 9863-1	0.45mm
Weight	EN ISO 9864	91g/m ²

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

